



Integrated CCS for Kansas (ICKan): CO₂ source assessment Preliminary design for capture from fossil fuel sources

Carbon Capture, Utilization and Storage in Kansas

Krish R. Krishnamurthy, Linde LLC

September 21, 2017

Wichita, KS

THE LINDE GROUP

Linde

ICKan Project Phase 1: CO₂ Sources & Capture Options Assessment - Objectives



Overall Objective

- Identify CO₂ emission sources and assess cost effective capture and compression options to provide 50 Million tonnes/CO₂ for the ICKan project CO₂ utilization and storage network

Specific Objectives

- Identify large single point CO₂ emissions sources (e.g. power plants and industrial CO₂ emissions) in Kansas state that can deliver the targeted captured CO₂ volumes for the ICKan EOR utilization /geological storage sites
- Obtain data from the source facilities for preliminary assessment of CO₂ capture and compression
- Perform conceptual design to assess CO₂ capture and compression costs.

Identified CO₂ sources for ICKan and characteristics

THE LINDE GROUP


Linde

CO ₂ Source	Key drivers	Challenges
Coal fired power plant Lead source: Westar's Jeffrey's Energy Center, St. Marys, KS (other coal plants available)	<ul style="list-style-type: none"> - Large single point source - Partial capture from one of the three-trains can enable meeting ICKan target 	<ul style="list-style-type: none"> - Cost of capture - Economic incentives - Contaminant & issues related to specific site design (aerosols) - Coal vs wind power economics in region
Refinery CHS SMR Hydrogen Plants (other sources, e.g. FCC boiler within refinery)	<ul style="list-style-type: none"> - Intermediate CO₂ volumes - Can contribute to ICKan target - Could promote economics with access to CO₂ pipeline 	<ul style="list-style-type: none"> - Non-SMR CO₂ sources distributed in site - Low pressure steam availability
Ethanol (Corn-based Fermentation plants)	<ul style="list-style-type: none"> - Significant number of lower volume but higher CO₂ concentration source ideal for pipeline aggregation - Bio-based may contribute to CO₂ footprint 	<ul style="list-style-type: none"> - Cost of specific contaminant removal if required (e.g. O₂, aldehydes, alcohols, H₂S/COS) - Low volumes and longer distances to market/storage sites

Pathways of CO₂ capture. Linde's technology portfolio.

THE LINDE GROUP

Linde



**Solvent based capture
is focus of this
presentation:**

- Applicable to new or retrofit plants
- Capture all or part of flue gas
- Applied at large scale in other applications
- Novel solvents (e.g. OASE® blue) stable in presence of flue gas contaminants & O₂
- Significant progress made toward the capture cost goal
- Recent successful large scale implementations (Boundary Dam, Petronova) provide confidence for future projects

BASF OASE[®] blue technology roadmap. Adopted & optimized for PCC applications.






THE LINDE GROUP

Linde

Equilibria

Kinetics

Stability



Lab. & Mini plant (2004)

- Ludwigshafen, Germany
- Solvent selection & performance verification



Pilot: 0.45 MWe (2009)

- Niederaussem, Germany
- Process opt., materials & emissions testing



Pilot: 1.5 MWe (2014-2016)

- Wilsonville, AL (NCCC)
- Design improvements, emissions confirmation



Large Pilot (proposed): 10+ MWe (2017-2020)

- Abbott power plant, UIUC, Champaign, IL
- Full value chain demo.




Linde-BASF progress toward lowering the cost of capture

THE LINDE GROUP

Linde

Reducing low pressure steam consumption:



Capex reduction:

- High capacity structured packing (smaller diameter absorbers)
- Higher pressure regeneration (Reduced CO₂ compressor cost)
- Novel lower cost equipment (e.g. reboiler, inter-stage heater)

Electrical energy reduction:

- CO₂ compression power by operating at higher regenerator pressure

Other features for lower Opex:

- Reduced solvent inventory
- Fast dynamics for load following

Westar Jeffrey's Energy Center: A large power plant CO₂ source capable to deliver the entire CO₂ capture volume required for ICKan through partial capture installation

THE LINDE GROUP

Linde

Power plant facts:

- 3 x 800 MWe power plants located in St. Marys, KS with a total nameplate annual CO₂ emissions of 12.5 million tonnes.
- Power plants built in the 1980's but fitted in the past decade with selective catalytic reduction (SCR) based NO_x removal, activated carbon sorbent based Hg removal and scrubber based flue gas desulfurization (FGD)

Capture opportunity:

- Partial CO₂ capture installation (~583 MWe flue gas) from one of the three power plants can satisfy the entire ICKan CO₂ integrated capture, compression and storage target over a 20 years project period
- Solvent based post-combustion capture likely technology option for implementation by 2025 due to technology maturity and capture capacity



Capture challenge:

- Not fitted with baghouse; potential aerosol in flue gas causing solvent carry-over and losses
- Concerns about the long term power plant utilization capacity with increasing wind power coming online

Overall integrated project economics:

- Sources of waste heat to generate low pressure steam for solvent regeneration, thereby reducing parasitic power consumption (e.g. full capacity waste heat utilization for partial CO₂ capture)

Westar Jeffrey's Energy Center: Preliminary CO₂ capture assessment/Design basis

THE LINDE GROUP

Linde

CO₂ product:

- 2.5 million MT (20 yrs) or 7500 MTPD
- 90% capture efficiency
- 99.7+% purity (<100 ppmv Oxygen)
- 150 bars delivery pressure at site boundary

Flue gas processed:

- Target flue gas flow rate: 2063 MT/hr (wet)
- Flue gas composition: CO₂ 10.8% wet; 13.2% dry
O₂ 5.1% wet; 6.3% dry
- Target capture plant capacity: 583 MWe (~73% of Unit 1)

Operating requirements:


- Regenerator LP steam (4.8 bar): 1.16 tons/ton CO₂
- Electrical power: 129 kW/ton CO₂ (40 MW)
- Cooling water: 112 m³/ton CO₂ (36,000 m³/hr)



Power plant block flow diagram showing potential waste heat extraction to generate LP steam for PCC plant

THE LINDE GROUP

Linde



CHS refinery: SMR H₂ plants can deliver cost effective CO₂ capture to partially meet the ICKan CO₂ capture volume target

THE LINDE GROUP

Linde

Steam Methane Reformer H₂ plant facts:

- 2 x ~40,000 Nm³/hr H₂ plant capacities. Plants incorporate PSA (Pressure swing adsorption) based H₂ purification with purge gas used as reformer fuel.
- Total name-plant CO₂ emissions with SMR furnace flue gases is ~760,000 Tonnes/year. This meets 30% of the ICKan CO₂ capture and storage capacity over a 20 year project.

Capture opportunity:

- Solvent based post-combustion capture from the reformer furnace flue gas will result in maximum CO₂ emissions reduction (~90% of total emissions from SMR H₂ plants).
- Sorbent based (pressure or vacuum swing adsorption) capture from syngas or purge gas are likely technology options for partial capture (~50-60% of total SMR H₂ plant emissions) as they are more cost effective than solvent based due to relatively smaller capture capacity.



Capture challenge:

- Non-H₂ plant refinery CO₂ emissions distributed and in smaller amounts
- Unfavorable steam balance necessitating separate generation of low pressure steam for CO₂ capture plant
- Current lower H₂ plant loading may affect scale of CO₂ capture

Overall integrated project economics:

- Shorter distance (access pipeline) to EOR and/or storage sites targeted.
- Additional steam generation for refinery needs combined with LP steam for solvent regeneration may be attractive.

CHS refinery SMR H₂ plant CO₂ capture: Preliminary assessment and design basis

THE LINDE GROUP

Linde

CO₂ product:


- 1872 MTPD (~13.6 million tons over 20 yrs)
- 90% capture efficiency
- 99.7+% purity (<100 ppmv Oxygen)
- 150 bars delivery pressure at site boundary

Flue gas processed (mixed from 2 SMR's):

- Target flue gas flow rate: 362.7 MT/hr (wet)
- Flue gas composition: CO₂ 15.8% wet; 19.1% dry
O₂ 2.2% wet; 2.7% dry
- Target capture plant capacity: 100% of available SMR H₂ plant furnace flue gases (2 plants)

Operating requirements:

- Regenerator LP steam (4.8 bar): 1.17 tons/ton CO₂
- Electrical power: 123 kW/ton CO₂ (9,600 kW)
- Cooling water: 115 m³/ton CO₂ (9000 m³/hr)



Questions?

THE LINDE GROUP

Linde

Thank you for your attention!

Back-up slides

Linde has performed number of large scale studies/
process concepts and engineering assessment tailor-
made based on end-customer requirements

THE LINDE GROUP

Linde

